

REVELASTIC TERRAZAS

Waterproof elastic covering

DESCRIPTION

Revelastic Terrazas is an elastic waterproof covering, without tar or bituminous products, and with a permanent elasticity.

Revelastic Terrazas comes in an easy-to-apply fluid paste which, once dry, forms a protective laminate, perfectly waterproof and elastic, without joints. Revelastic Terrazas can be elongated by more than 300% and offers a perfect resistance to bad weather, aging, ultraviolet rays, city and industrial centre atmospheres. Revelastic Terrazas has a good resistance to abrasion and perforation and is able to support considerable movement as long as it is not used as paving.

RECOMMENDED USES

Applications Revelastic Terrazas is suitable for the waterproofing of roofs, terraces, dividing walls, window-box sealing, and acts as a protective addition to metallic roofs.

APPLICATION METHODS

The surface must be in good condition, free from dust, oil, non-adhesive materials etc. Apply prior coatings (at least three coats are recommended) of Revelastic Terrazas, either with a roller, brush or spray gun, until the desired thickness is reached, The drying time of Revelastic Terrazas depends on the temperature and environmental humidity so applications should be separated by 8 to 16 hours. In dry weather and high temperatures two coats can be applied per day.

At times of environmental humidity or winter it is not advisable to apply if dew has fallen before it is dry.

Dilution and tool cleaning: Water

SPECIFICATION DATA

COLOUR: White, Rust, Grey and Green.

CONTAINER: 750, 4, 15, and 18 Lts.

COVERAGE: 7 - 9 m² per litre depending on the condition and surface type.

DRYING TIME: 1 hour.

REPAINT TIME: 6 - 8 hours.

SOLVENT: Water.

INFLAMMABILITY: Not totally flameproof.

SHELF LIFE: Approximately 5 to 6 years in well-sealed containers.

MINIMUM WORK TEMPERATURE: Not below +5° c.

DENSITY: 1.200 – 1.400 g/cm³.

Temperature, ambient humidity and paint thickness etc. can cause changes in drying time and coverage.

2004/42IIA (i) (140/140) Máx. COVs 100g/l.

Fire resistance; M-1.



PINTURAS BAÑOS, S. L.

FACTORY: Pol. Ind. Los Urreas Sierra de Carrascoy, nº 8

OFFICES: Jiménez de Gregorio 6. SAN JAVIER (MURCIA) ESPAÑA Tlf.968 190 707 – Fax. 968 190 068

www.pinturasbanos.com E-MAIL: pinturasbanos@pinturasbanos.com

In line with the provisions of the ADR these merchandises can be transported by road if the condition of its container and label conform to prescribed norms.

The information provided in this technical leaflet is the result of investigation in our laboratories and real application experiments. Given that products are frequently used in conditions not under our control, we cannot guarantee more than the effective result of the product as long as it is applied in the correct way.

Keep out of the reach of children. Only to be used in well-ventilated areas. In the event of ingestion, go immediately to the doctor and show him the label or container.

REVIEW: 1	DATE: 12/09/2009	PAGES: 1/1
-----------	------------------	------------

