

BRICOMAX

Matt plastic paint

DESCRIPTION

A well-covering matt plastic paint, made with polymerised acrylic styrene resins in water dispersion. It is completely water resistant, rain impermeable and vapour permeable, resisting erosion and wearing even in the most aggressive of environments. Indicated for the protection of exteriors, home interiors and commercial premises.

APPLICATION METHODS

Stir the contents of the container well until a consistent blend is achieved.
Eliminate dust, grease, saltpetre and other imperfections in bad condition.
Apply with a brush or roller depending on the practicalities of each case.
On new mortar or plaster surfaces, apply two coats: the first diluted by 15% and the second by 8% maximum.
On old painted surfaces, scrape off and completely remove flakes and badly sticking areas then proceed as for new surfaces.

SPECIFICATION DATA

COLOUR: White.
CONTAINER: 4, 15 Lts.
COVERAGE: 7 - 9 m² per litre depending on the condition and surface type.
DRYING TIME: 1/2 hour.
REPAINT TIME: 3 - 4 hours.
SOLVENT: Water.
INFLAMMABILITY: Not totally flameproof.
SHELF LIFE: Approximately 5 to 6 years in well-sealed containers.
MINIMUM WORK TEMPERATURE: Not below +5° c.
DENSITY: 1.300 – 1.700 g/cm³.
pH: 7-9.5

Temperature, ambient humidity and paint thickness etc. can cause changes in drying time and coverage.

2004/42IIA (A) (75/30) Max. COVs 18g/l.

Fire resistance; M-1.

---/---



PINTURAS BAÑOS, S. L.

FACTORY: Pol. Ind. Los Urreas Sierra de Carrascoy, nº 8

OFFICES: Jiménez de Gregorio 6. SAN JAVIER (MURCIA) ESPAÑA Tlf.968 190 707 – Fax. 968 190 068

www.pinturasbanos.com E-MAIL: pinturasbanos@pinturasbanos.com

In line with the provisions of the ADR these merchandises can be transported by road if the condition of its container and label conform to prescribed norms.

The information provided in this technical leaflet is the result of investigation in our laboratories and real application experiments. Given that products are frequently used in conditions not under our control, we cannot guarantee more than the effective result of the product as long as it is applied in the correct way.

Keep out of the reach of children. Only to be used in well-ventilated areas. In the event of ingestion, go immediately to the doctor and show him the label or container.

REVIEW: 2	DATE: 12/05/2010	PAGES:
-----------	------------------	--------



PINTURAS BAÑOS, S. L.

FACTORY: Pol. Ind. Los Urreas Sierra de Carrascoy, nº 8

OFFICES: Jiménez de Gregorio 6. SAN JAVIER (MURCIA) ESPAÑA Tlf.968 190 707 – Fax. 968 190 068

www.pinturasbanos.com **E-MAIL:** pinturasbanos@pinturasbanos.com